



EQUIPMENT

MEAT & BONE SAW P140-5-SS



This P140-5 "SS" model is the most expensive top notch unit. This model features an all stainless steel construction: cabinet, head, and (sealed) motor compartment, along with its workhorse of a 5 HP motor. It's ideally suited for fish processing plants, highly corrosion resistant even in a salt-water or high humidity environment. These machines can be dismantled for cleaning without tools, and can be hosed down whenever necessary. Known for its high volume meat processing in tough conditions. Additional features include precision balanced cast iron saw wheels to eliminate vibration, ensuring a steady blade drive & protection. Also, the easy slide system (fully stainless steel rollers) allow for a precise moving table ride, reducing effort and increasing productivity. Minimum maintenance, durable/ideal for continuous work and built to last.

STANDARD FEATURES

- 3550 mm (139.76" x .5/8") saw blade
- Heavy duty, floor standing
- 5 HP motor 3.72 Kw three phase
- Stainless steel body/construction
- Easy to clean: Hose down washable
- Friction resistant saw guides
- Waste tray
- Stainless steel fixed table



Tensioning system
Easily adjustable
Assures a proper blade tension for a clean cut and a long lasting blade life.



Thermomagnetic switches
Protect the motor from overloads. Easily activated.



Removable wheel and blade cleaners system
To keep wheel and blade, grease and waste-free.




Disassembles easily
Main components are easily disassembled (Without tools) for cleaning and sanitizing, and saw blade can be replaced without the need to disassemble any of the components

MEAT & BONE SAW P140-5-SS

Technical Data

| | |
|------------------------------|---|
| Saw blade (Inches) | 3550 mm (139.76" x .5/8") |
| Blade speed | 20 m/sec (65.62 ft/sec) |
| Throat width (Inches) | 410 mm (16.14") |
| Throat height (Inches) | 480 mm (18.9") |
| Table dimensions (WxL) | 1010 mm x 555 mm (39.76" x 21.85") |
| Switch type | Thermomagnetic |
| Finish | Stainless steel |
| Waste tray | Yes |
| Movable blade guard | Yes |
| Sealed off bearings | Yes |
| Non slip silent V-belt drive | Yes |
| Net weight (Shipping) | 250 Kg (280 Kg) 551.16 lbs. (617.29 lbs.) |
| Voltage | 230/50/60/3 or 380-440/50/60/3 |

Detail & Dimensions



Safety & Sanitation
Conforms UL
std 763

Conforms
NSF-8

Conforms CAN/CSA
STD C22.2

As continued product improvement is a policy of Powerline, specifications are subject to change without notice.



POWERLINE EQUIPMENT COMPANY

Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480

www.powerlineequip.com